



# Single-phase String Inverter **X1-Smart**

**Powerful Single  
Phase Inverter**



Low Start-Up  
Voltage



High  
Efficiency



Flexible  
Communication



Remote  
Monitoring

## **X1-SMART (6.0kW / 7.0kW / 8.0kW)**

- Remote upgrade and maintenance
- 150% DC oversizing and 110% AC overloading
- Support Meter/CT and zero injection control
- Small and compact size
- Easy to install and setup
- Support EV Charger (Fast Charging Mode)





# X1-SMART (SINGLE-PHASE)

X1-6.0-T-D  
X1-6.0-T-N

X1-7.0-T-D  
X1-7.0-T-N

X1-8.0-T-D  
X1-8.0-T-N

## DC INPUT

Max. PV array input power [Wp]	9000	10500	12000
Max. PV input voltage [V]	550	550	550
Startup voltage [V]	100	100	100
Nominal input voltage [V]	360	360	360
MPP tracker voltage range [V]	100~530	100~530	100~530
No. of MPP trackers/Strings per MPP tracker	2(1/2)	2(1/2)	2(1/2)
Max. input current(input A/input B) [A]	12/24	12/24	12/24
Max. short circuit current(input A/input B) [A]	14/28	14/28	14/28

## AC OUTPUT

Nominal AC output power [W]	6000	7000	8000
Nominal AC output current [A]	26	30	34.7
Max. AC output apparent power [VA]	6600	7700	8800
Max. AC output current [A]	28.7	33.5	38.3
Nominal AC voltage [V]	220V/230/240,160~285		
Nominal grid frequency/Grid frequency range [Hz]	50/60; ±5		
Displacement power factor	0.8 leading~0.8 lagging		
THDi (rated power) [%]	<3		

## SYSTEM DATA

Max. efficiency [%]	97.40	97.40	97.40
Euro. efficiency [%]	96.80	96.80	96.80
Standby consumption [W] @Night	<1		
Ingress protection	IP65		
Operating temperature range [°C]	-25~60 (derating at 45)		
Max. operation altitude [m]	≤2000		
Humidity [%]	0~100 (non-condensing)		
Typical noise emission [dB]	<40		
Storage temperature [°C]	-25~60		
Dimensions(WxHxD) [mm]	401*450*190		
Weight [kg]	22		
Cooling concept	Nature cooling		
Communication interfaces	RS485/USB/DRM/CT/(Optional: Pocket WiFi/LAN)		

## PROTECTION

Over/under voltage protection	YES
DC isolation protection	YES
Monitoring ground fault protection	YES
Grid monitoring	YES
DC injection monitoring	YES
Back feed current monitoring	YES
Residual current detection	YES
Anti-islanding protection	YES
Over temp protection	YES

## STANDARD

Safety	IEC/EN 62109-1/-2
EMC	EN61000-6-1/2/3/4;EN61000-3-2/3/11/12
Certification	AS4777.2/EN 61000-3-2/EN 61000-3-3/EN 61000-3-11/EN 61000-3-12/EN 61000-6-1/EN 61000-6-2/EN 61000-6-3

\* V2.0. Information may be subject to modify without notice.